

# EUROROOF SELF-ADHESIVE OLIVINE CAP SHEET



**ALUMASC**  
ROOFING

EurorooF Self-Adhesive High Performance Roofing Systems comprise a premium self-adhesive, CO<sub>2</sub> neutralising, reinforced SBS polymer modified bituminous waterproofing membrane, underlays, insulation boards and air and vapour control layers (AVCL). Specifically developed to meet the need for improved safety by using flame-free installation methods and removing the need for a naked flame. The system is fully adaptable to meet the individual requirements of every project for use across all building sectors in both refurbishment and new-build roofing and waterproofing projects.

## ✓ Where to Specify

- New Build
- Refurbishment
- Cold roofs
- Warm roofs (all roofing insulations)
- Overlay of existing waterproofing systems
- Compatible with all conventional roofing substrates


## ✓ Durability

When installed on stable substrates and regularly maintained, the system will have a life in excess of 25 years.

## ✓ Environmental Benefits

EurorooF Self-Adhesive Olivine is surfaced with a natural olivine granule, a magnesium iron silicate. The Olivine granules cause a chemical reaction in CO<sub>2</sub> in rainwater which converts it to silicon dioxide (sand) and magnesium carbonate, two products harmless to the environment.


1m<sup>2</sup> of Olivine has the capacity capture to approx. 1.75kg of CO<sub>2</sub>.



Typical Assembly	
4	EurorooF Self-Adhesive Olivine Cap Sheet
3	EurorooF Self-Adhesive Underlay
	EurorooF SA Primer
2	PIR Insulation (type GTF) or Class A fire rated alternative
	PU Insulation Adhesive
1	Self-Adhesive AVCL
	EurorooF SA Primer

# EUROROOF SELF-ADHESIVE OLIVINE CAP SHEET


Other Common System Types



## Insulated Overlay of Existing Waterproofing

4	EurorooF Self-Adhesive Olivine Cap Sheet
3	EurorooF Self-Adhesive Underlay
	EurorooF SA Primer
2	PIR Insulation (type GTF) or Class A fire rated alternative
	PU Insulation Adhesive
1	Existing waterproofing

**NB.** Air & Vapour Control Layer may be required, subject to condition of the existing waterproofing.



## Cold Overlay of Existing Waterproofing

3	EurorooF Self-Adhesive Olivine Cap Sheet
2	EurorooF Self-Adhesive Underlay
	EurorooF SA Primer
1	Existing waterproofing

### Approvals

• Fire classification of **B<sub>roof</sub>(t4)** in accordance with BS EN 13501-5



### Warranties

Alumasc offers a comprehensive range of single-source warranty options for up to 25 Years. Installed exclusively by Registered Contractors and underpinned by Alumasc's extensive project support service, Alumasc warranties cover product, workmanship, and design.

### Technical Support

Alumasc Technical Services can advise on all aspects of product selection, specification and integration of Alumasc systems into any building design.