

# Product Datasheet

## Alumasc Termination Bar

Sheet No: PD301FR  
Issued: Nov 2023  
Pages: 1 of 1

### Description

Alumasc Termination Bar is available in either aluminium or GRP.

### Use

For use as a continuous mechanical termination of Alumasc waterproofing membranes at the head of upstand details.

Note: Upstand details should terminate a minimum of 150mm from the adjacent finished roof level. Where this is not possible, authorisation from the specifier and building control must be in place. In all cases, any warranty issued for the Alumasc waterproofing will cover entry of water through the upstand membrane, but not over it.

### Application

Fix the termination bar securely into place at 150mm centres with stainless steel screws of a type and length as appropriate for the substrate into which they are to be installed, to be confirmed by the specialist fixing supplier. Drill pilot holes and plug as necessary, in accordance with the fixing supplier's recommendations.

The termination bars must be continuous and level.

Any cut ends (such as at corners) must be filed smooth and rounded to eliminate any sharp edges.

### Storage

Store in a clean, dry, secure location.

### Product Data

Type	Aluminium
Length	1500 mm

Type	GRP
Length	3000 mm

### Health & Safety

Safety Data Sheets are available upon request and can also be downloaded directly from [www.alumascroofing.com](http://www.alumascroofing.com).

### Technical Support

Technical advice is available from Alumasc Technical Services at:

Telephone: +44 (0)1744 648400

Email: [technical@alumascroofing.com](mailto:technical@alumascroofing.com)

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.