

Product Data Sheet

Caltech QC Metal Primer

Sheet No: PDFR704
Issued: April 2024
Pages: 1 of 1

Description

Caltech Metal Primer is a cold liquid applied, rust inhibiting, lead and chromate free metallic primer.

Use

For the priming of prepared/weathered, non-rusted steel, galvanised metal, aluminium etc. Not for use on heavily corroded metal, or non-ferrous metals such as copper, lead etc.

Application

- Apply one coat of Caltech Metal Primer at an approximate coverage rate of 0.09 l/m², by brush or short pile roller. Ensure all exposed metal panel edges, cut ends, bolt heads and sharp angles etc. are fully primed.
- Rainproof time: approx. 60 minutes, next coat approx. 60 minutes.
- Rough or highly porous surfaces will significantly reduce the coverage rates. Touch-in suspect areas where necessary.

Storage

- Flammable/combustible – Keep away from oxidisers, heat and flames.
- Store in tightly closed original container in a dry, cool and well-ventilated place.
- Keep in original container.
- Avoid contact with oxidising agents.
- Transport class: UN1263.

Product Data

Drum size	3 litres
Colour	Light Grey
Shelf life	24 months in unopened drums

Health & Safety

Safety Data Sheets are available upon request and can also be downloaded directly from www.alumascroofing.com.

Technical Support

Technical advice is available from Alumasc Technical Services at:

Telephone: +44 (0)1744 648400

Email: technical@alumascroofing.com

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.