

Product Datasheet

Eurorof Caltech Preparation Layer

Sheet No: PD511FR
Issued: July 2021
Pages: 1 of 1

Description

Eurorof Caltech Preparation Layer is a self-adhesive aluminium faced preparation layer, with a removable plastic film on the underside.

Use

For use as a preparation layer over approved Alumasc FF (foil-faced) and Alumasc GTF (glass tissue faced) rigid urethane thermal insulation in warm roof Caltech systems.

Approvals

- British Board of Agrément Certificate No. 13/5038.

Application

- Remove backing and apply to the clean and dry surface of the foil faced insulation board, ensuring full contact without air pockets, creases or wrinkles, with 60mm side laps and 150mm end laps.
- If applying in temperatures of 5°C or less, foil faced insulation boards must first be primed with Caltech Insulation Primer at a rate of 0.1l/m².
- Glass tissue faced boards must always be primed with Eurorof SA Primer.
- Apply the Caltech Base Coat and Top Coat/s as per the project specification.

Storage

- Store upright in original packaging in a dry area, ideally between 10 and 30°C.
- Storage class: n/a - not hazardous
- Transport class: n/a - not hazardous

Product Data

Size	40 x 1.08m
Thickness	0.6mm
Colour	Foil faced
Roll Weight	25kg
Shelf life	12 months

Health & Safety

Safety Data Sheets are available upon request and can also be downloaded directly from www.alumascroofing.com.

Technical Support

Technical advice is available from Alumasc Technical Services at:

Telephone: +44 (0)1744 648400

Email: technical@alumascroofing.com

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.