

# Product Datasheet

## Eurorof Caltech Solvent

Sheet No: PD514FR  
Issued: July 2021  
Pages: 1 of 1

### Description

Eurorof Caltech Solvent is a single component blend of Xylene and Methoxy Propyl Acetate, clear in colour.

### Uses

For the activation of synthetic surfaces prior to overlaying with Caltech as directed in the project specification where appropriate, and also for the cleaning of tools used for the application of Caltech/Acrytite cold-applied liquid waterproofing systems.

### Approvals

- British Board of Agrément Certificate No. 13/5038

### Application

- Applied by brush or roller.
- Two or more applications might be necessary on very contaminated substrates.
- Allow to dry completely before overcoating.

### Storage and Transport

- Flammable/combustible – Keep away from oxidisers, heat and flames.
- Store in tightly closed original container in a dry, cool and well-ventilated place.
- Keep in original container.
- Avoid contact with oxidising agents.
  
- Storage class: Flammable liquid storage.
- The storage and conditions must meet the statutory requirements of The Highly Flammable Liquids and Petroleum Gases Regulations 1972.
- Transport class: UN1263

### Product Data

Drum size	5 and 25 litres
Colour	Clear
Flash Point	28°C
Solids Content	n/a
Density	0.969kg/l
Shelf life	2 years in unopened drums
VOC Content	Max 969gm/l

### Health & Safety

Safety Data Sheets are available upon request and can also be downloaded directly from [www.alumascroofing.com](http://www.alumascroofing.com).

### Technical Support

Technical advice is available from Alumasc Technical Services at:

Telephone: +44 (0)1744 648400

Email: [technical@alumascroofing.com](mailto:technical@alumascroofing.com)

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.