

AIRTILE VILLA


A Modern Roman Style Profile



ALUMASC
ROOFING

✓ Where to Specify

- Educational Buildings
- Social Housing
- Commercial Buildings
- Flat to Pitch
- Community Centres
- Modular Buildings
- Vertical Cladding



AIRTILE VILLA

A Modern Roman Style Profile



Advantages

- British made
- Designed to give a traditional slate appearance
- Lightweight
- Low pitch
- Good vandal resistance (0.9mm steel base)
- Quick installation
- Virtually maintenance free
- Extensive range of accessories and flashings available
- Fully dry-fixed
- 60+ Year life expectancy
- Guaranteed for 40-years against weather penetration


Technical Data

- Minimum pitch 10°
- Maximum pitch 90°
- Overall width: 1295mm
- Cover width: 1200mm
- Side lap: 95mm
- Step: 24mm
- Batten gauge (0.45mm): 370mm
- Batten gauge (0.9mm): 368mm
- Individual tile width: 100mm
- Roof cover per tile panel: 0.44m²
- Tile panels per m²: 2.25
- Steel base: 0.45mm & 0.9mm
- Weight as laid per m²: 7kg & 11kg
- Fire resistance: AA classification equal to traditional roof tiles and slates

Approvals

- BBA Certificate No. 02/3917
- Manufactured using ISO 9001 approved materials
- ISO 14001

Colours Available



Technical Support

Alumasc Technical Services can advise on all aspects of product selection, specification and integration of Alumasc systems into any building design.